



CooVox V2 Series Expansion Box – EX16S



Introduction

CooVox EX16S is a FXS port expansion box especially designed for ZYCOO CooVox series IPPBX system. Each box provides 16 FXS channels for connecting analog phones and fax machines to your CooVox IPPBX system as extensions through your LAN. It enables the analog extensions with all IP extension features.

Highlights

- Auto-provisioning: Provisioning by ZYCOO CooVox-V2 series IP-PBX, zero-config on the box.
- Feature rich and ease of use: Inherits nearly all innovative VoIP call features from the CooVox V2 series IPPBX system.
- Robust and reliable: 1GHz A7 processor on board guarantees superior user experience.
- Expandable: Each EX16S connects to CooVox V2 system through your LAN, you can expand FXS ports by deploying several EX16S boxes in your LAN till fulfill all analog phones and Fax machines you have.

Specifications

Processor	1GHz dual-core A7 processor
Memory	512MB DDR3 SDRAM
Storage	8GB SD card
Lines	16 x RJ11 FXS
Network	2 x 10/100Mbps
Signaling	SIP(RFC3261)
Audio Codecs	G.722/G.711-Ulaw/G.711-Alaw/G.726/G.729/GSM/SPEEX
Dimension	280 x 150 x 65mm
Mounting	Desktop and rack-mountable
Power	DC 12V/3.5A
Compatible ZYCOO IP-PBX's	CooVox-U20V2, CooVox-U50V2, CooVox-U60V2, CooVox-U80, CooVox-U100V2

How it Works

